

DADI E TIRANTI PER FLANGE PORTADIAFRAMMA CALBRATO A NORMA ANSI B 16.36
STUD BOLTS FOR ORIFICE METER WITH ORIFICE PLATE ACCORDING TO STANDARD ANSI B 16.36

	Classe - Class 150				Classe - Class 300				Classe - Class 600			
	Tirante - Stud bolt		L		Tirante - Stud bolt		L		Tirante - Stud bolt		L	
	D	N°	RF	RJ	D	N°	RF	RJ	D	N°	RF	RJ
1"	-	-	-	-	5/8"	4	130	150	5/8"	4	135	150
1" 1/2	-	-	-	-	3/4"	4	135	155	3/4"	4	140	155
2"	-	-	-	-	5/8"	8	130	155	5/8"	8	135	155
3"	-	-	-	-	3/4"	8	135	160	3/4"	8	140	160
4"	-	-	-	-	3/4"	8	135	160	7/8"	8	155	165
6"	-	-	-	-	3/4"	12	135	160	1"	12	180	190
8"	-	-	-	-	7/8"	12	155	175	1"1/8"	12	205	220
10"	-	-	-	-	1"	16	175	190	1"1/4"	16	230	235
12"	-	-	-	-	1"1/8"	16	185	205	1"1/4"	20	235	240
14"	-	-	-	-	1"1/8"	20	190	220	1"3/8"	20	250	260
16"	-	-	-	-	1"1/8"	20	205	230	1"1/2"	20	270	280
18"	1"1/8"	16	165	190	1"1/4"	24	220	235	1"5/8"	20	295	300
20"	1"1/8"	20	180	205	1"1/4"	24	225	250	1"5/8"	24	305	320
22"	1"1/4"	20	190	215	1"1/2"	24	245	275	1"3/4"	24	325	340
24"	1"1/4"	20	200	220	1"1/2"	24	255	280	1"7/8"	24	350	365
26"	1"1/4"	24	235	-	1"5/8"	28	280	315	1"7/8"	28	365	385
28"	1"1/4"	28	245	-	1"5/8"	28	295	325	2"	28	375	395
30"	1"1/4"	28	250	-	1"3/4"	28	315	345	2"	28	385	400

	Classe - Class 900				Classe - Class 1500				Classe - Class 2500			
	Tirante - Stud bolt		L		Tirante - Stud bolt		L		Tirante - Stud bolt		L	
	D	N°	RF	RJ	D	N°	RF	RJ	D	N°	RF	RJ
1"	-	-	-	-	7/8"	4	155	160	7/8"	4	155	160
1" 1/2	-	-	-	-	1"	4	160	165	1"1/8"	4	180	190
2"	-	-	-	-	7/8"	8	155	165	1"	8	185	200
3"	7/8"	8	155	165	1"1/8"	8	185	200	1"1/4"	8	230	245
4"	1"1/8"	8	180	190	1"1/4"	8	205	220	1"1/2"	8	255	280
6"	1"1/8"	12	205	210	1"3/8"	12	270	280	2"	8	350	370
8"	1"3/8"	12	235	245	1"5/8"	12	305	325	2"	12	395	410
10"	1"3/8"	16	250	255	1"7/8"	12	350	365	2"1/2"	12	505	530
12"	1"3/8"	20	270	275	2"	16	390	410	2"3/4"	12	555	580
14"	1"1/2"	20	290	305	2"1/4"	16	420	445				
16"	1"5/8"	20	300	320	2"1/2"	16	475	500				
18"	1"7/8"	20	345	365	2"3/4"	16	510	540				
20"	2"	20	365	385	3"	16	560	585				
22"	-	-	-	-	-	-	-	-				
24"	2"1/2"	20	460	485	3"1/2"	16	635	675				
26"	2"3/4"	20	480	505								
28"	3"	20	490	520								
30"	3"	20	500	535								

1

-

150

-

RF

-

WN

-

05

-

2N

**Diametro Nominale
Size**

1"	14"
1" 1/2	16"
2"	18"
3"	20"
4"	22"
6"	24"
8"	26"
10"	28"
12"	30"

**Pressione
ANSI - Rating**

150 - 150
300 - 300
600 - 600
900 - 900
1500 - 1500
2500 - 2500

**Accoppiamento
Facing**

Faccia risalto Flat-face - RF
Anello di giunzione Ring joint - RJ

**Tipo
Type**

Saldare di testa Welding neck - WN
Sovrapposizione Welding socket - SO

**Materiali
Material**

A 105 - 05
AISI 304 - 04
AISI 304 L - 06
AISI 316 - 16
AISI 316 L - 17
MONEL - 400
DUPLEX - 22
Altri-Other - 00

**Prese pressione std.
Pressure taps**

2N - n°2 of 180° 1/2" NPT-F
2SW - n°2 of 180° 1/2" SW
00 - Altre a richiesta Other on request

1

-

150

-

05

**Diametro Nominale
Size**

1"	14"
1" 1/2	16"
2"	18"
3"	20"
4"	22"
6"	24"
8"	26"
10"	28"
12"	30"

**Pressione
ANSI - Rating**

150 - 150
300 - 300
600 - 600
900 - 900
1500 - 1500
2500 - 2500

**Tipo
Type**

L7-GR7 - 02
L7-GR4 - 03
B8-GR8 - 04
B7-2H - 05
B16-GR4 - 11